



TARASCON - COLOR: RIVIÈRE - PATTERN# 6016731X

TARASCON

CLASSIC YET CASUAL


BASKETWEAVE MOTIF



TARASCON - COLOR: NATUREL - PATTERN# 6016739X



TARASCON - COLOR: BLÉ - PATTERN# 6016724X





TARASCON - COLOR: AMBRE - PATTERN# 6016722X

OVERVIEW TARASCON

The pattern on the Tarascon plank is created by assembling small LVT planks, each enhanced with micro-beveling and in-register embossing, onto the rigid ISOCORE panel, which really elevates the hardwood realism and warmth of the product.



TARASCON - COLOR: NATUREL - PATTERN# 6016739X



TARASCON - COLOR: AMBRE - PATTERN# 6016722X




TARASCON - COLOR: RIVIÈRE - PATTERN# 6016731X



TARASCON - COLOR: BLÉ - PATTERN# 6016724X

TARASCON (BASKETWEAVE PLANK GRANDE)



TECHNICAL DATA SHEETS - US

Find more information about ASPECTA™ CONTOURS and our other collections on aspectaflooring.com.

PHYSICAL PROPERTIES & PACKAGING (FLOATING MULTILAYER MODULAR FLOORING - 8.0 MM / 0.55 MM)

Collection	Chambord	Chantilly	Versailles	Tarascon
Use	Commercial	Commercial	Commercial	Commercial
Size (inches)	8.46 x 42.32 in.	8.66 x 43.31 in.	12.01 x 55.43 in.	11.89 x 55.83 in.
Size (mm)	215 x 1075 mm	220 x 1100 mm	305 x 1407.8 mm	302 x 1418 mm
Thickness - Wear Layer	0.55 mm (22 mil)	0.55 mm (22 mil)	0.55 mm (22 mil)	0.55 mm (22 mil)
Thickness - Overall	8.0 mm (0.315 in.)	8.0 mm (0.315 in.)	8.0 mm (0.315 in.)	8.0 mm (0.315 in.)
Top Layer	2.0 mm (0.079 in.) LVT	2.0 mm (0.079 in.) LVT	2.0 mm (0.079 in.) LVT	2.0 mm (0.079 in.) LVT
Core	5.0 mm (0.197 in.) ISOCORE	5.0 mm (0.197 in.) ISOCORE	5.0 mm (0.197 in.) ISOCORE	5.0 mm (0.197 in.) ISOCORE
Pad	1.0 mm (0.039 in.) HDPE	1.0 mm (0.039 in.) HDPE	1.0 mm (0.039 in.) HDPE	1.0 mm (0.039 in.) HDPE
Profile	Micro-bevel	Micro-bevel	Micro-bevel	Micro-bevel
Finish	Duraspect™	Duraspect™	Duraspect™	Duraspect™
Embossing	In-Register	In-Register	In-Register	In-Register
Coverage - Carton	8 Pieces (19.9 Sq.ft. / 1.85 Sq.m.)	8 Pieces (20.84 Sq.ft. / 1.94 Sq.m.)	4 Pieces (18.49 Sq.ft. / 1.72 Sq.m.)	5 Pieces (23.05 Sq.ft. / 2.14 Sq.m.)
Coverage - Pallet	52 Cartons (1,034.9 Sq.ft. / 96.1 Sq.m.)	52 Cartons (1,083.6 Sq.ft. / 100.7 Sq.m.)	45 Cartons (831.9 Sq.ft. / 77.3 Sq.m.)	36 Cartons (829.7 Sq.ft. / 77.1 Sq.m.)
Coverage - Container	16 Pallets (16,559 Sq.ft. / 1,538 Sq.m.)	20 Pallets (21,672 Sq.ft. / 2,013 Sq.m.)	18 Pallets (14,975 Sq.ft. / 1,391 Sq.m.)	21 Pallets (17,424 Sq.ft. / 1,619 Sq.m.)
ASPECTA™ Contours Limited Commercial Warranty ¹	Material: 20 Years (100%) Labor: 10 Years (Pro-Rated)	Material: 20 Years (100%) Labor: 10 Years (Pro-Rated)	Material: 20 Years (100%) Labor: 10 Years (Pro-Rated)	Material: 20 Years (100%) Labor: 10 Years (Pro-Rated)

NORTH AMERICAN STANDARDS - MANUFACTURING & USAGE (ASTM F3261)

Standard	Description	Requirements	Results
ASTM F3261	Physical Characteristics / Tolerances	Refer to Standard	Passes Requirements ²
ASTM F1914	Residual Indentation	Average: ≤ 0.007 in. (0.18 mm)	Passes Requirements
ASTM F1914	Surface Integrity	No puncture through wear layer / décor layer	Passes Requirements
ISO 23999	Dimensional Stability	≤ 0.2% / lineal ft. (305 mm)	Passes Requirements
ISO 23999	Curling	≤ 0.080 in. (2.0 mm)	Passes Requirements
ASTM F925	Chemical Resistance	No more than "Slight Change"	Passes Requirements
ASTM F1514 / ASTM F1515	Resistance to Heat / Resistance to Light	Average ΔE < 8.0	Passes Requirements
ASTM F970	Static Load Limit	≤ 0.005 in. (0.13 mm), 250 psi	Passes Requirements (≥ 500 psi)

Notes

1) ASPECTA™ CONTOURS Limited Commercial Warranty: Please see full terms and conditions of our warranties at www.aspectaflooring.com.

2) ASTM F3261 - Physical Characteristics / Tolerances: includes Size, Squareness, Thickness, Wear Layer Thickness (Commercial Class.), Flatness, Openings, and Ledging.

TECHNICAL DATA SHEETS - US

Find more information about ASPECTA™ CONTOURS and our other collections on aspecta flooring.com.

NORTH AMERICAN STANDARDS - SAFETY & PERFORMANCE

Standard	Description	Requirements	Results
ASTM E648	Critical Radiant Flux (Radiant Panel)	Class I: ≥ 0.45 W/Sq.cm.	Passes Requirements ³
ASTM E662	Smoke Density	Flaming & Non-Flaming ≤ 450	Passes Requirements ⁴
CDPH Standard Method v1.2	VOCs/TVOCs, Formaldehyde	Refer to Standard	Passes Requirements
ASTM F963	Heavy Metals	Refer to Standard (Table I)	Passes Requirements
CPSC-CH-C1001-09.3	Phthalates	Per CPSIA ⁵ : $\leq 0.1\%$ per Substance	Passes Requirements
ASTM D2047	Coefficient of Friction / Slip Resistance	N/A (No Official Requirements)	≥ 0.6 (Dry)
ANSI ESD STM97.2	Body Voltage	N/A (No Official Requirements)	Average (Abs): 1.3kV

NORTH AMERICAN STANDARDS - SOUND

Assembly	ASTM E90	ASTM E492	ASTM E2179	Results (Remarks)
6" Concrete Slab	STC 50	IIC 54	Δ IIC 25	Tested assemblies pass International Building Code (IBC)
6" Concrete Slab + Drop-Ceiling	STC 61	IIC 67	Not Applicable	Requirements of STC ≥ 50 and IIC ≥ 50 for multi-story dwellings

Notes

3) ASTM E648 - Critical Radiant Flux (Radiant Panel): Passes Requirements for Class I per International Building Code (IBC) 2018 & NFPA 101 Life Safety Code.

4) ASTM E662 - Smoke Density: 450 is the limit established by many state, county, and/or local building and/or fire codes in the United States, but is not set as a limit for (resilient) flooring products nationwide. Thus, Smoke Density requirements for flooring products may vary from jurisdiction to jurisdiction.

5) CPSC-CH-C1001-09.3 - Phthalates: CPSIA = Consumer Product Safety Improvement Act.






TECHNICAL DATA SHEETS - EU

Find more information about ASPECTA™ CONTOURS and our other collections on aspectaflooring.com.

PHYSICAL PROPERTIES & PACKAGING (FLOATING MULTILAYER MODULAR FLOORING - 8.0 MM / 0.55 MM)

Collection	Chambord	Chantilly	Versailles	Tarascon
Use ¹	Commercial	Commercial	Commercial	Commercial
Size (inches)	8,46 x 42,32 in.	8,66 x 43,31 in.	12,01 x 55,43 in.	11,89 x 55,83 in.
Size (mm)	215 x 1075 mm	220 x 1100 mm	305 x 1407,8 mm	302 x 1418 mm
Thickness - Wear Layer	0,55 mm (22 mil)	0,55 mm (22 mil)	0,55 mm (22 mil)	0,55 mm (22 mil)
Thickness - Overall	8,0 mm (0,315 in.)	8,0 mm (0,315 in.)	8,0 mm (0,315 in.)	8,0 mm (0,315 in.)
Top Layer	2,0 mm (0,079 in.) LVT	2,0 mm (0,079 in.) LVT	2,0 mm (0,079 in.) LVT	2,0 mm (0,079 in.) LVT
Core	5,0 mm (0,197 in.) ISOCORE	5,0 mm (0,197 in.) ISOCORE	5,0 mm (0,197 in.) ISOCORE	5,0 mm (0,197 in.) ISOCORE
Pad	1,0 mm (0,039 in.) HDPE	1,0 mm (0,039 in.) HDPE	1,0 mm (0,039 in.) HDPE	1,0 mm (0,039 in.) HDPE
Profile	Micro-bevel	Micro-bevel	Micro-bevel	Micro-bevel
Finish	Duraspect™	Duraspect™	Duraspect™	Duraspect™
Embossing	In-Register	In-Register	In-Register	In-Register
Coverage - Carton	8 Pieces (19,9 Sq.ft. / 1,85 m ²)	8 Pieces (20,84 Sq.ft. / 1,94 m ²)	4 Pieces (18,49 Sq.ft. / 1,72 m ²)	5 Pieces (23,05 Sq.ft. / 2,14 m ²)
Coverage - Pallet	52 Cartons (1034,9 Sq.ft. / 96,15 m ²)	52 Cartons (1083,6 Sq.ft. / 100,67 m ²)	45 Cartons (831,9 Sq.ft. / 77,29 m ²)	36 Cartons (829,7 Sq.ft. / 77,08 m ²)
Coverage - Container	16 Pallets (16.559 Sq.ft. / 1538,37 m ²)	20 Pallets (21.672 Sq.ft. / 2013,44 m ²)	18 Pallets (14.975 Sq.ft. / 1391,19 m ²)	21 Pallets (17.424 Sq.ft. / 1619,73 m ²)
ASPECTA™ Contours Limited Commercial Warranty ²	Material: 20 Years (100%) Labor: 10 Years (Pro-Rated)	Material: 20 Years (100%) Labor: 10 Years (Pro-Rated)	Material: 20 Years (100%) Labor: 10 Years (Pro-Rated)	Material: 20 Years (100%) Labor: 10 Years (Pro-Rated)

EUROPEAN / INTERNATIONAL STANDARDS - CE CERTIFICATION / TESTING

Description	Standard	Symbol	Requirements	Results
CE Certification	EN 14041		Refer to Standards Below	Refer to Results Below
Reaction to Fire (and Smoke Production)	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2		B_{fl} - s1 Classification Critical Flux: ≥8.0kW/m ² Flame Spread: ≤150mm within 20s Smoke value as % x min: ≤750	Passes Requirements
Content of PCP (Pentachlorophenol)	EN 14041		<5ppm	Passes Requirements
Formaldehyde Emission	EN 717-1		Class E1: Release ≤0.124mg/m ³	Passes Requirements
Slip Resistance (Dry)	EN 13893		Class DS: Coefficient of Friction ≥ 0.30	Surpasses Requirements

Notes

1) Use: Refer to Recommended Use PDF for Recommended Commercial Areas

2) ASPECTA™ CONTOURS Limited Commercial Warranty: Please see full terms and conditions of our warranties at www.aspectaflooring.com.

TECHNICAL DATA SHEETS - EU

Find more information about ASPECTA™ CONTOURS and our other collections on [aspecta flooring.com](https://www.aspecta flooring.com).






EUROPEAN / INTERNATIONAL STANDARDS - MANUFACTURING & USAGE (EN 16511)

Description	Standard	Symbol	Requirements	Results
Classification (Level of Use)	EN 16511 EN ISO 10874		Commercial - Very Heavy (Class 34) Refer to Standards Below	Passes Requirements (Refer to Results Below)
Wear Resistance IP, Method A	EN 13329, Annex E		≥4,000 cycles	Surpasses Requirements
Impact Resistance (Big Ball)	EN 13329+A1, Annex F		≥1800mm	Surpasses Requirements
Micro-Scratch Resistance [Class]	EN 16094, Method B	N/A	≤MSR-B2	Passes
Castor Chair Resistance	EN 425		After 25,000 cycles: No Disturbance to the Surface; No Delamination, Cracks, or Disruptions	Passes Requirements
Effect of Furniture Leg	EN 424		No Visible Damage	Passes Requirements
Residual Indentation	EN ISO 24343-1		≤0.15mm	Surpasses Requirements
Resistance to Staining [Grade, per Group]	EN 438-2 (Group 1 - Only 10 Minutes)		Groups 1, 2 & 3: Grade 5	Passes Requirements
Locking Strength	ISO 24334		Long Side ≥ 2.0kN/m Short Side ≥ 3.5kN/m	Surpasses Requirements
Dimensional Stability Due to Variation of Temperature	EN ISO 23999		≤0.25%	Surpasses Requirements
Thickness (t)	ISO 24337		$\Delta t_{avg} \leq 0.50\text{mm}$ (Versus Nominal) $t_{max} - t_{min} \leq 0.50\text{mm}$	Passes Requirements
Length (l)	ISO 24337		$l \leq 1500\text{mm}: \Delta l \leq 0.5\text{mm}$ $l > 1500\text{mm}: \Delta l \leq 0.3\text{mm/m}$ (Versus Nominal)	Passes Requirements
Width (w)			$\Delta w_{avg} \leq 0.10\text{mm}$ (Versus Nominal) $w_{max} - w_{min} \leq 0.20\text{mm}$	Passes Requirements
Squareness (q)			$q_{max} \leq 0.20\text{mm}$	Passes Requirements
Straightness (s)			$s_{max} \leq 0.30\text{mm/m}$	Passes Requirements
Flatness (f)	ISO 24337	N/A	Maximum Single Values: $f_{w,concave} \leq 0.15\%$, $f_{w,convex} \leq 0.20\%$ $f_{l,concave} \leq 0.50\%$, $f_{l,convex} \leq 1.00\%$	Passes Requirements
Openings (o)	ISO 24337	N/A	Measured from the Surface Between Vertical, Contacting Edges: $o_{avg} \leq 0.15\text{mm}$, $o_{max} \leq 0.20\text{mm}$	Passes Requirements
Height Difference (h)	ISO 24337	N/A	$h_{avg} \leq 0.10\text{mm}$ $h_{max} \leq 0.15\text{mm}$	Passes Requirements

TECHNICAL DATA SHEETS - EU

Find more information about ASPECTA™ CONTOURS and our other collections on aspecta flooring.com.

EUROPEAN / INTERNATIONAL STANDARDS - AUXILIARY PERFORMANCE & SAFETY

Description	Standard	Symbol	Requirements	Results
Slip Resistance (Wet)	DIN 51130	N/A	Grade R10: $\geq 10^\circ$ and $< 19^\circ$	Passes / Surpasses
Slip Resistance (Australia / New Zealand)	AS 4586	N/A	Wet Pendulum (Slider 96) P3: 35-44 SRV Oil-Wet Inclining Platform Grade R10: $\geq 10^\circ$ and $< 19^\circ$	Passes / Surpasses Requirements
Thermal Resistance Thermal Conductivity	EN 12664		N/A	0.074 (m ² .K/W) 0.108 (W/m.k)
Static Electrical Propensity	EN 1815, Method A		$\leq 2.0\text{kV}$	Passes Requirements
Colour Fastness to Light	ISO 105-B02, Method 3		\geq Grade 6	Passes Requirements
Impact Sound Insulation ³	EN ISO 10140-3 ISO 717-2 EN ISO 140-8		N/A	$\Delta L_w = 18\text{dB}$
A-weighted walking sound pressure level	EN 16205:2013		N/A	$L_{n,walk,A} = 85\text{dB(A)}$
Product-Content Safety	REACH SVHC 201	N/A	Refer to Standard	Passes Requirements
Heavy Metals	EN71-3	N/A	Refer to Standard	Not detected

STANDARDS - SUSTAINABILITY

Standard(s)	Description
FloorScore® SCS-FS-03808	This product is FloorScore® Certified and has thus been found to comply with the volatile organic compound emissions criteria of the California Section 01350 standard.

*Patent pending PCT/EP2019/062703 & NL2020972

Notes

3) Impact Sound Insulation (EN ISO 10140-3, ISO 717-2, EN ISO 140-8): ΔL_w = Weighted Reduction of Impact Sound Pressure Level

ASPECTA™ - THE TRANSPARENCY LEADER

ASPECTA™ and its commitment to transparency are a force of positive disruption in the global LVT-flooring market. There are no communication barriers between you and us. We openly declare product ingredients. We tell you where our products are made. We provide policies and metrics on factory worker diversity, equity, and benefits. We measure the products' impact on the environment over its life cycle and communicate openly about it. We voluntarily provide this information with labels attached to our products, on the ASPECTA™ website and in sustainability databases. We encourage others to participate in the conversation.

We are the transparency leader.



Indoor Air Certification

ASPECTA™ fulfills the VOC emissions European criteria by world market leader Eurofins. The same organization also awarded ASPECTA™ the best-in-class low emissions certificate: Indoor Air Comfort GOLD.



HPD (Health Product Declaration)

ASPECTA™ ONE, ASPECTA™ FIVE and ASPECTA™ TEN products carry a voluntary Health Product Declarations (HPD) Open Standard label, which contains product ingredients and associated health information.



REACH

REACH (EC 1907/2006) aims to improve the protection of human health and the environment through the better and earlier identification of the intrinsic properties of chemical substances. This is done by the four processes of REACH, namely the registration, evaluation, authorisation and restriction of chemicals. All our products are reach compliant.

Just.

JUST Label

ASPECTA™ is the first company in the world to obtain a JUST label, a voluntary transparency tool, for an Asian factory. JUST provides assurance that we are paying attention to what matters most: social factors such as diversity, equity, and safety. Created by the International Living Future Institute (ILFI), JUST is the beginning of a new era in transparency, and ASPECTA™ is leading the way.

Declare.

Declare Label

We declare each and every ingredient in the ASPECTA™ ONE, ASPECTA™ FIVE and ASPECTA™ TEN product lines. Declare Labels, created by the International Living Future Institute (ILFI) are clear and informative „nutrition labels“ for building products. As a leader in global transparency, ASPECTA™ is the first to translate these labels into six European languages with a seventh, Mandarin, in the works.



ISO9001

Quality management system



ISO14001

Environmental management system