

LL55 EXCELLENCE LOOSE-LAY LVT


TECHNICAL DATA SHEET

PHYSICAL PROPERTIES & PACKAGING (LOOSE-LAY 5.0 MM/0.55 MM)		
Collection	EXCELLENCE PLANK	EXCELLENCE TILE - XL
Use	Commercial & Residential	Commercial & Residential
Size	228.6mm x 1219.2mm (9" x 48")	457.2mm x 914.4mm (18" x 36")
Wear Layer - Thickness	0.55mm	0.55mm
Thickness - Overall	5.0mm	5.0mm
Edge Detail	4 sides Micro Bevel	4 sides Micro Bevel
Finish	Duraspect™ Extreme Surface Protectant	Duraspect™ Extreme Surface Protectant
Embossing(s)	Natural Timber	Natural Timber
Mass per Unit Area	9740 g/m ²	9740 g/m ²
Pieces/Carton	7 Pieces	5 Pieces
Coverage/Carton	1.95m ²	2.09m ²
Coverage/Pallet	40 Cartons (78.00m ²)	50 Cartons (104.52m ²)
Coverage/Container	24 Pallets (1872 m ²)	19 Pallets (1986 m ²)
Warranty ⁽¹⁾	Material: 20 years (100%) Labour: 10 years (Pro rata)	Material: 20 years (100%) Labour: 10 years (Pro rata)

EUROPEAN / INTERNATIONAL STANDARDS - MANUFACTURING & USAGE				
Description	Standard	Symbol	Requirements	Results
CE Certification	EN 14041		Refer to Standards Below	Refer to Results Below
Reaction to Fire (and Smoke Production)	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2		Bfl - s1 Classification Critical Flux: ≥8.0kW/m ² Flame Spread: ≤150mm within 20s Smoke Value as % x min: ≤750	Passes Requirements
Content of PCP (Pentachlorophenol)	EN 14041		<0.1ppm	Passes Requirements
Formaldehyde Emission	EN 717-1		Class E1: Release ≤0.124mg/m ³	Passes Requirements
Slip Resistance (Dry)	EN 13893		Class DS: Coefficient of Friction ≥0.3	Passes Requirements
Thermal Resistance	EN 12667		N/A	0.01745 m ² K/W at 10°C (tile) 0.0145 m ² K/W at 10°C (plank)

LL55 EXCELLENCE LOOSE-LAY LVT

TECHNICAL DATA SHEET

EUROPEAN / INTERNATIONAL STANDARDS – CE CERTIFICATION / TESTING				
Description	Standard	Symbol	Requirements	Results
Classification (Level of Use)	EN ISO 10582 EN ISO 10874		Commercial - Heavy (Class 42) Wear Layer (Nominal): $\geq 0.55\text{mm}$ Thickness (Nominal): $\geq 2.0\text{mm}$	Passes Requirements
Size, Squareness, and Straightness	EN ISO 24342		Size: $\leq 0.15\%$ from Nominal Squareness/Straightness: If Size $> 400\text{mm}$: $\leq 0.35\text{mm}$ If Size $\leq 400\text{mm}$: $\leq 0.25\text{mm}$	Passes Requirements
Thickness	EN ISO 24346		Average (from Nominal): $+0.13\text{mm} / -0.10\text{mm}$ Any Sample (from Average): $\pm 0.15\text{mm}$	Passes Requirements
Mass per Unit Area	EN ISO 23997		9571g/m^2	Passes Requirements
Dimensional Stability	EN ISO 23999		$\leq 0.25\%$	Passes Requirements
Curling	EN ISO 23999	N/A	$\leq 2\text{mm}$	Passes Requirements
Flexibility	EN ISO 24344 (Method A)		No Cracks (20mm Mandrel)	Passes Requirements
Residual Indentation	EN ISO 24343-1		$\leq 0.1\text{mm}$	Passes Requirements
Castor Chair	ISO 4918		After 25,000 Cycles: Delamination – None Appearance $\leq$ “Slight Change”	Passes Requirements
Colour Fastness to Light	ISO 105-B02, Method 3		$\geq$ Grade 6	Passes Requirements

LL55 EXCELLENCE LOOSE-LAY LVT

TECHNICAL DATA SHEET

EUROPEAN / INTERNATIONAL STANDARDS – AUXILIARY PERFORMANCE & SAFETY				
Description	Standard	Symbol	Requirements	Results
Slip Resistance (Wet)	DIN 51130	N/A	Grade R10: $\geq 10^\circ$ and $< 19^\circ$	Passes Requirements
Slip Resistance (Australia / New Zealand)	AS 4586	N/A	Wet Pendulum (Slider 96) P3: 35-44 SRV Oil-Wet Inclining Platform Grade R10: $\geq 10^\circ$ and $< 19^\circ$	Passes Requirements
Chemical Resistance	EN ISO 26987 / EN 423		N/A	No Effect
Abrasion / Wear Resistance	EN 660-2		N/A	Fv $\leq 2.0\text{mm}^3/100\text{r}$
Static Electrical Propensity	EN 1815, Method A		N/A	Average: $< 2\text{kV}$
Impact Sound Insulation ⁽²⁾	EN ISO 10140-3 ISO 717-2 EN ISO 140-8		N/A	$\Delta L_W = 11\text{dB}$
A-weighted walking sound pressure level	EN 16205:2013		N/A	$L_{n,\text{walk}, A} = 82\text{ dB(A)}$

Footnotes

1) Warranty: Please see full terms and conditions of our warranties at www.aspecta flooring.com

2) Impact Sound Insulation (EN ISO 10140-3, ISO 717-2, EN ISO 140-8): ΔL_W = Weighted Reduction of Impact Sound Pressure Level

The manufacturing facility is ISO 9001 (Quality Management System) and ISO 14001 (Environmental Management System) certified.



Just.

Declare.

